

GL



1500 ÷ 2000 kg

ø max 2 cm



mod:	 cm	 Kg	 l/1'	 bar
GL 60	60	65	35	180
GL 80	80	91	35	180

UT



2400 ÷ 4000 kg

ø max 3/4 cm



mod:	 cm	 Kg	 l/1'	 bar
UT 80	80	170	50	220
UT 100	103	197	60	220
UT 125	126	227	60	220
UT 150	150	360	80	220

UT F



2500 ÷ 4000 kg

ø max 10/12 cm



mod:	 cm	 Kg	 l/1'	 bar
UT 100 F	103	284	80	220
UT 125 F	126	340	80	220


FT



7000 ÷ 10000 kg

ø max 15/20 cm



mod:	 cm	 Kg	 l/1'	 bar
FT 130	136	593	100	350
FT 160	163	693	100	350
FT 200	199	771	130	350
FT 230	226	850	130	350

WT



15000 ÷ 20000 kg

ø max 25/30 cm



mod:	 cm	 Kg	 l/1'	 bar
WT 130	129	934	100	350
WT 160	160	1100	100	350
WT 180	180	1195	130	350
WT 225	224	1397	130	350




GL super



2000 ÷ 3000 kg

ø max 2 cm



mod:	 cm	 Kg	 l/1'	 bar
GL 60 Super	60	115	35	180
GL 80 Super	80	162	35	180


UT super



3000 ÷ 6000 kg

ø max 3/4 cm



mod:	 cm	 Kg	 l/1'	 bar
UT 100 Super	103	296	60	220
UT 125 Super	126	341	60	220
UT 150 Super	150	391	80	220



UT F super



3000 ÷ 6000 kg

ø max 10/12 cm



mod:	 cm	 Kg	 l/1'	 bar
UT 100 F Super	103	394	80	220
UT 125 F Super	126	450	80	220
UT 150 F Super	150	510	80	220



KT



10000 ÷ 18000 kg

ø max 15/20 cm



mod:	 cm	 Kg	 l/1'	 bar
KT 210	210	1126	150	350
KT 240	240	1194	150	350



WTS



15000 ÷ 20000 kg

ø max 25/30 cm



mod:	 cm	 Kg	 l/1'	 bar
WTS 200	200	1215	150	350